



Manufactured of reinforced Polypropylene

Multiple housing colors and port sizes

HYDRONIX HF3 SERIES SLIM RIB CAP FILTER HOUSINGS

Are available in a variety of colors and are made to house 2.5" diameter cartridges. Most 9 7/8" and 10" cartridges fit easily and caps are available in 1/4", 3/8", 1/2" and 3/4" female NPT ports.

HYDRONIX HF3 SERIES SLIM RIB CAP FILTER HOUSINGS

Are ideal for typical applications as pre and post-filtration for RO systems, under sink filters, countertop systems, ice machines, food service and other applications.

HYDRONIX HF3 SERIES SLIM RIB CAP FILTER HOUSINGS

Have pressure relief (PR) buttons available for 1/2" and 1/4" port housings.



HF3 SERIES

Slim Rib Cap Filter Housings

Materials of Construction

Opaque Housing:	Polypropylene
Clear Housing:	San
Cap:	Polypropylene
O-Ring:	EPDM
Maximum Temperature:	125°F (51.7°C)
Maximum Pressure:	75 PSI (5.17 bar)

Applications

- Reverse Osmosis
- Residential Plumbing
- Photography
- Beverage
- Ice Maker
- Misting Units

HF3 SERIES SPECIFICATIONS		
	Part Number	Description
5"	HF3-5WHWH14	5" White Body, White Rib Cap 1/4"
	HF3-5WHWH38	5" White Body, White Rib Cap 3/8"
	HF3-5WHWH12	5" White Body, White Rib Cap 1/2"
	HF3-5CLWH14	5" Clear Body, White Rib Cap 1/4"
	HF3-5CLWH38	5" Clear Body, White Rib Cap 3/8"
	HF3-5CLWH12	5" Clear Body, White Rib Cap 1/2"
10" 1/4" Port	HF3-10WHWH14	10" White Body, White Rib Cap 1/4"
	HF3-10BLBK14	10" Blue Body, Black Rib Cap 1/4"
	HF3-10CLWH14	10" Clear Body, White Rib Cap 1/4"
	HF3-10CLBK14	10" Clear Body, Black Rib Cap 1/4"
10" 3/8" Port	HF3-10WHWH38	10" White Body, White Rib Cap 3/8"
	HF3-10BLBK38	10" Blue Body, Black Rib Cap 3/8"
	HF3-10CLWH38	10" Clear Body, White Rib Cap 3/8"
	HF3-10CLBK38	10" Clear Body, Black Rib Cap 3/8"
10" 1" PORT	HF3-10WHWH12	10" White Body, White Rib Cap 1/2"
	HF3-10WHWH12PR	10" White Body, White Rib Cap 1/2", PR
	HF3-10BLBK12	10" Blue Body, Black Rib Cap 1/2"
	HF3-10CLWH12	10" Clear Body, White Rib Cap 1/2"
	HF3-10CLWH12PR	10" Clear Body, White Rib Cap 1/2", PR
	HF3-10CLBK12	10" Clear Body, Black Rib Cap 1/2"
10" 3/4" Port	HF3-10CLBK12PR	10" Clear Body, Black Rib Cap 1/2", PR
	HF3-10WHWH34	10" White Body, White Rib Cap 3/4"
	HF3-10WHWH34PR	10" White Body, White Rib Cap 3/4", PR
	HF3-10BLBK34	10" Blue Body, Black Rib Cap 3/4"
	HF3-10CLWH34	10" Clear Body, White Rib Cap 3/4"
	HF3-10CLWH34PR	10" Clear Body, White Rib Cap 3/4", PR
	HF3-10CLBK34	10" Clear Body, Black Rib Cap 3/4"
	HF3-10CLBK34PR	10" Clear Body, Black Rib Cap 3/4", PR
	HF2/3 ORING	O-Ring for HF2, 3 Filter Housing

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

* Special lengths and diameters available.

Model # Guide

Filter Housing	Body Cart Length	Cap Color	Pressure Relief Button
HF3	10	WH	12 PR
Housing Style	Body Color	Connection Type	
3 = Slim Rib Cap	WH - White	14 = 1/4"	
5 = 5"	BK - Black	38 = 3/8"	
10 = 10"		12 = 1/2"	
		34 = 3/4"	

LEGEND

Housing Style:	3 = Slim Rib Cap	Cap Color:	WH - White
Body Length:	5 = 5"		BK - Black
	10 = 10"	Connection Type:	14 = 1/4"
Body Color:	WH - White		38 = 3/8"
	CL - Clear		12 = 1/2"
	BL - Blue		34 = 3/4"

Installation Guidelines

WARNING: READ THESE INSTRUCTIONS BEFORE CHANGING OR INSTALLING. FOLLOW THESE INSTRUCTIONS TO REDUCE RISK OF DANGER.

Caution: filter housing must be protected against freezing and extreme temperatures. Filter housings should not be in direct contact with sunlight for a prolonged period of time since uv rays can make housings brittle. Pressure should always be measured before installation and water pressure regulators should be installed in the main line or in front of the housing if water pressure exceeds manufacturers' maximum water pressure: 75 psi. Installers should make sure filters and replacement filters are the correct length and are not too long so as to not cause undo strain and stress on the housing. A leak detector must be installed on all installations where high pressure, water hammer and pressure spikes are known or suspected to be present and on all installations where pressure is over 60 psi. Failure to the above may result in cracking of the filter housing, water leakage and water damage.

Caution: all filtration systems contain other parts that have a limited service life. Exhaustion of the service life of those parts often cannot be easily detected. Commonly, it is only after leakage has been observed or water damage has occurred that one is made aware that the service life has been exhausted.

Important notice: to prevent costly repairs or possible water damage we strongly recommend that the bowl or sump of all plastic housings be replaced periodically: every 5 years for clear sumps, and every 4 years for opaque sumps. If your sump has been in use for more than the recommended period, it should be replaced immediately. Be sure to date any new or replacement sump for future reference and indicate the next recommended replacement date.

Warranty: limited three (3) year warranty from the date of sale for material defects only. Warranty is limited to repair or replacement of product only. Any misuse, misinstallation, lack of maintenance, exceeding maximum pressure or failure to follow these instructions will void limited warranty.

DISCLAIMER OF WARRANTIES. Except as expressly warranted in writing by Hydronix water technology, the goods sold by Hydronix water technology are purchased by the buyer "as is." Hydronix water technology does not warrant that the goods are of merchantable quality or that they can be used for any particular purpose. Except as expressly warranted in writing by Hydronix water technology, Hydronix water technology makes no representation or warranty of any kind with respect to the products.

LIMITATION OF LIABILITY. In no event shall Hydronix water technology be liable to the purchaser or any other entity for more than the invoice price received by Hydronix water technology for any non-conforming products. Hydronix water technology shall not be liable to the purchaser or any other entity for personal injury, property damage, or any direct, indirect, special, incidental, consequential, punitive, exemplary, or other damages of any kind, including without limitation the cost of procurement of substitute goods, the loss of profits, products, or production, or the interruption of business, however caused and on any theory of liability, and whether or not Hydronix water technology has been advised of the possibility of such damages. The essential purpose of this provision is to limit the liability of Hydronix water technology arising out of the sale of products to the purchaser whether for breach of contract, negligence, or otherwise. These limitations shall apply notwithstanding any failure of essential purpose of any limited remedy and notwithstanding the provisions of any other agreement between Hydronix water technology and the purchaser.

Distributed by:

HYDRONIX WATER TECHNOLOGY

P.O. Box 2235 Chino Hills, CA 91709 | USA

sales@hydronixwater.com • www.HydronixWater.com